

View Online at <https://aerobasegroup.com/nsn/5930-01-314-7706>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

1.812 inches

Overall Height:

1.000 inches

Overall Width:

0.937 inches

Overall Diameter:

1.000 inches

Individual Section Quantity:

2

Operating Temperature Range:

-65.0/+85.0 degrees celsius

End Application:

2gvortac, fa-9996/3

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

8 single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

50.0 milliamperes resistive load ac at altitude

Special Features:

Open construction without sealed shaft and panel seal; 45 degrees angle of throw; 25,000 rotational life cycles; vibration grade 10 to 2,000 hz frequency range; shock type medium impact; insulation material glass laminate; altitude 70,000 ft; cocentric shaft; reference data, 3a2s1, ti-6820.2, fa-9996, vprtav, vor/dme, vor eq., vol 8, sec 8, pg 8-428

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A052b0