

View Online at <https://aerobasegroup.com/nsn/5930-01-314-8165>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Moisture resistant and salt spray resistant and vibration resistant

**Overall Length:**

0.575 inches

**Overall Height:**

2.300 inches

**Overall Width:**

0.535 inches

**Bushing Length:**

0.470 inches

**Body Length:**

0.575 inches

**Body Width:**

0.535 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

1.090 inches

**Actuator Width:**

0.535 inches

**Actuator Position-action Relationship:**

Up position momentary and down position momentary and center position maintained

**Actuator Position-locking Relationship:**

Up position no locking action and down position no locking action and center position locked in

**Actuator Color:**

White single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

0.740 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

**Precious Material And Location:**

Terminal surfaces gold and contacts silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0