

View Online at <https://aerobasegroup.com/nsn/5930-01-315-1445>

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

5.360 inches

Overall Height:

2.230 inches

Overall Width:

4.220 inches

Unthreaded Mounting Hole Diameter:

0.219 inches

Distance Between Mounting Facility Centers:

2.750 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -30.0 degrees fahrenheit and 200.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

400.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

500.0 milliamperes resistive load third voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+7.00/+30.00 actuation point inches of water

Contact Adjustment Type:

Internal actuation point hex nut with scale

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0