NSN 5930-01-315-1452

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-315-1452

Hazardous Locations/environmental Protection:
Shock proof
Overall Length:
3.520 inches
Overall Height:
1.740 inches
Overall Width:
2.120 inches
Unthreaded Mounting Hole Diameter:
0.189 inches single mounting facility
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
1.620 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.250 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob and legend plate
Contact Voltage Rating In Volts:
440.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Terminal Type:
Tab w/screw
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
750.0 milliamperes resistive load highest ac voltage rating at sea level
Special Features:
Legend plate reads dl byp/test
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5930-01-315-1452

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0