

View Online at <https://aerobasegroup.com/nsn/5930-01-315-3034>

**Overall Length:**

1.188 inches

**Overall Height:**

0.656 inches

**Body Diameter:**

0.625 inches

**Mounting Slot Width:**

0.140 inches

**Body Height:**

0.375 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Distance Between Mounting Facility Centers:**

0.937 inches

**End Application:**

2 generation vortac (2gvortac)

**Temperature Sensing Element Type:**

Internal sensor

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 400.0 degrees fahrenheit

**Mounting Method:**

Bracket and slot and unthreaded hole

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

2.0 amperes resistive load third voltage and 1.0 amperes inductive load third voltage and 0.5 amperes lamp load third voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

210.00 actuation point degrees fahrenheit and 185.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Special Features:**

Subminiature, type i, bimetallic, 2 amperes

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Disc w/flange

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fii:**

A048b0