

View Online at <https://aerobasegroup.com/nsn/5930-01-315-3044>

Overall Length:

1.750 inches

Overall Height:

2.375 inches

Overall Width:

1.875 inches

Individual Section Quantity:

1

Operating Temperature Range:

-65.0/+85.0 degrees celsius

End Application:

Ssr-dmti solid state receiver/digital moving target indicator

Switch Contact Basic Design:

Coded

Pole Quantity:

2 single section in-line

Throw Quantity:

1 single section in-line

Mounting Method:

Bracket single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Switch Actuator Indexing Position Quantity:

10 single actuator

Terminal Type:

Printed circuit

Contact Switching Action:

Breaks before makes single section in-line

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Contact Arrangement Truth Table:

Decimal, 2 pole - 10 positions single section

Special Features:

Glossy black case; opaque white letters marking indicating wheel; thumbwheel bi-directional switch assembly; rotary switch code indicating; nonsealed; non-illuminating; style sprc11; 50, 000 rotational life cycles at neg 65 degrees cent to pos 85 degrees cent; vibration frequency range 10-2, 000 hz; shock type high impact; altitude up to 10, 000 ft

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A052b0