

View Online at <https://aerobasegroup.com/nsn/5930-01-315-3231>

Thread Class:

2a single mounting facility

Thread Length:

0.292 inches single mounting facility and 0.332 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.737 inches

First Flat Length:

0.230 inches single actuator and 0.270 inches single actuator

Flat Height:

0.084 inches single actuator and 0.104 inches single actuator

Shaft Diameter:

0.123 inches single actuator and 0.126 inches single actuator

Shaft Length:

0.355 inches single actuator and 0.395 inches single actuator

Overall Diameter:

0.800 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Operating Temperature Range:

-65.0/+125.0 degrees celsius

End Application:

Sonar set an/bqq-6

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

3 single section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Detent Rotational Torque Range:

+0.320/+1.700 inch-pounds single actuator

Switch Actuator Stop Device Type:

Fixed-adjustable stops single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level and 250.0 milliamperes inductive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Test Data Document:

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef single mounting facility

Specification Data:

81349-mil-s-3786/13 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A052b0