## NSN 5930-01-315-6373

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-315-6373 **Thread Class:** 2a single threaded stud **Overall Height:** 0.692 inches **Body Height:** 0.437 inches **Overall Diameter:** 0.640 inches **End Application:** Periscope **Tempurature Sensing Element Type:** Internal sensor **Operating Tempurature Rating:** Between -65.0 degrees fahrenheit and 500.0 degrees fahrenheit **Mounting Method:** Threaded stud Thready Qty Per Inch (tpi): 32 single threaded stud **Contact Action Stimulus:** Increase **Thread Size:** 0.138 inches single threaded stud **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally open, momentary action **Terminal Type:** Tab, solder lug **Contact Load Current Rating:** 5.0 amperes resistive load third voltage and 2.5 amperes inductive load third voltage and 1.0 amperes lamp load third voltage **Contact Adjustability:** Actuation point not adjustable and deactuation point not adjustable **Contact Stimulus Rating:** 160.00 actuation point degrees fahrenheit and 150.00 deactuation point degrees fahrenheit **Contact Voltage Rating In Volts:** 28.0 dc at sea level second voltage Frequency In Hertz: 60.0 first voltage Media For Which Designed: Gas or liquid

Style Designator:

Disc

Thread Series Designator:

Unc single threaded stud

## NSN 5930-01-315-6373

Thermostatic Switch - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
No Fiig:

Mil-std (military Standard): Mil-s-24236 spec.