Rotary Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-315-7437

atertight	
verall Length:	
450 inches	
verall Height:	
300 inches	
verall Width:	
700 inches	
nthreaded Mounting Hole Diameter:	
230 inches single mounting facility	
dividual Section Quantity:	
ongest Horizontal Distance Between Mounting Cente	rs:
000 inches single mounting facility	
ongest Vertical Distance Between Mounting Centers:	
700 inches single mounting facility	
ounting Method:	
ange single mounting facility and unthreaded hole single	mounting facility
eatures Provided:	i i i i i i i i i i i i i i i i i i i
ctuator knob and legend plate and spring return	
ontact Voltage Rating In Volts:	
0.0 highest ac voltage rating at sea level	
witch Actuator Momentary Position:	
ockwise single actuator and counterclockwise single actu	uator
ounting Facility Pattern:	
our position rectangular single mounting facility	
witch Actuator Indexing Position Quantity:	
single actuator	
witch Actuator Positioning Increment:	
0.0 degrees single actuator	
ontact Load Current Rating:	
0.0 amperes inductive load lowest dc voltage rating at sea	a level
pecial Features:	
gend plate reads: stop, start	
nelf Life:	
a	
nit Of Measure:	
emilitarization:	
)	
ig:	
052b0	