

View Online at <https://aerobasegroup.com/nsn/5930-01-316-0972>

Overall Length:

2.405 inches

Outside Diameter:

0.500 inches single connection

Overall Height:

4.000 inches

Overall Width:

1.937 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -40.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Threaded stud

Contact Action Stimulus:

Decrease

Proof Pressure:

450.00 pounds per square inch

Thread Size:

0.500 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

500.0 milliamperes inductive load third voltage

Contact Adjustability:

Actuation point adjustable, preset and deactuation point adjustable, preset

Contact Adjustment Range:

+10.00/+235.00 actuation point pounds per square inch and +11.00/+250.00 deactuation point pounds per square inch

Contact Adjustment Type:

External actuation point serrated nut and external deactuation point serrated nut

Contact Stimulus Rating:

35.00 actuation point pounds per square inch

Contact Voltage Rating In Volts:

480.0 ac at sea level second voltage

Pressure Connector Type:

External seat-gasket seal, threaded external single connection

Special Features:

Single pressure connection is also threaded internally with npt 0.125-27 thread

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0