

View Online at <https://aerobasegroup.com/nsn/5930-01-316-1753>

**Thread Class:**

2b 1st mounting facility

**Hazardous Locations/environmental Protection:**

Shock resistant

**Overall Length:**

4.125 inches

**Overall Height:**

2.500 inches

**Overall Width:**

3.000 inches

**Unthreaded Mounting Hole Diameter:**

0.203 inches 2nd mounting facility

**Distance Between Mounting Facility Centers:**

2.094 inches 2nd mounting facility

**Individual Section Quantity:**

8

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Facility Circle Radius:**

1.164 inches 1st mounting facility

**Mounting Method:**

Bracket 2nd mounting facility and unthreaded hole 2nd mounting facility

**Features Provided:**

Actuator knob and dummy section

**Thready Qty Per Inch (tpi):**

24 1st mounting facility

**Thread Size:**

0.190 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

120.0 dc at sea level

**Mounting Facility Pattern:**

Two position in-line 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Makes before breaks each section periphery

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load dc at sea level

**Special Features:**

Item must comply with requirements of defense electronics supply center production standard no. L04178; for navy nuclear propulsion plant products only

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unc 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0