

View Online at <https://aerobasegroup.com/nsn/5930-01-316-1754>

Thread Class:

2b single mounting facility

Overall Length:

0.480 inches

Overall Height:

1.680 inches

Overall Width:

1.310 inches

Distance Between Mounting Facility Centers:

1.040 inches single mounting facility

Individual Section Quantity:

1

Operating Temperature Range:

-65.0/+85.0 degrees celsius

End Application:

6920-01-299-2216 lpa trainer; weapon system-multiple launch rocket system (mlrs)

Mounting Method:

Threaded hole single mounting facility

Actuator Type:

Push button single actuator

Thready Qty Per Inch (tpi):

56 single mounting facility

Thread Size:

0.086 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7 single section

Contact Arrangement Truth Table:

Bcd with complement, 2 pole - 8 positions single section

Color:

White single indicator marking

Style Designator:

Rectangular indicating

Test Data Document:

81349-mil-s-22710 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single mounting facility

Specification Data:

81349-mil-s-22710/17 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0