

View Online at <https://aerobasegroup.com/nsn/5930-01-316-2987>

**Thread Class:**

2b single mounting facility

**Overall Length:**

10.530 inches

**Overall Height:**

3.750 inches

**Overall Width:**

3.750 inches

**Individual Section Quantity:**

15

**Longest Horizontal Distance Between Mounting Centers:**

2.300 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.300 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

24 single mounting facility

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

345.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section periphery

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

4.0 amperes resistive load highest ac voltage rating at sea level

**Special Features:**

Item must comply with requirements of defense electronics supply center production standard no. L04175; for navy nuclear propulsion plant products only

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0