NSN 5930-01-316-2987



Rotary Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-316-2987 **Thread Class:** 2b single mounting facility **Overall Length:** 10.530 inches **Overall Height:** 3.750 inches **Overall Width:** 3.750 inches **Individual Section Quantity:** 15 **Longest Horizontal Distance Between Mounting Centers:** 2.300 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.300 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 single mounting facility **Thread Size:** 0.190 inches single mounting facility **Contact Voltage Rating In Volts:** 345.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

6 single actuator

Criticality Code Justification:

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

4.0 amperes resistive load highest ac voltage rating at sea level

NSN 5930-01-316-2987

Rotary Switch - Page 2 of 2



S	pe	cial	Fe	atui	es
---	----	------	----	------	----

Item must comply with requirements of defense electronics supply center production standard no. L04175; for navy nuclear propulsion plant products only

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0