

View Online at <https://aerobasegroup.com/nsn/5930-01-316-6710>

**Overall Length:**

5.000 inches

**Overall Height:**

2.250 inches

**Overall Width:**

5.000 inches

**Unthreaded Mounting Hole Diameter:**

0.406 inches

**Longest Horizontal Distance Between Mounting Centers:**

3.800 inches

**Longest Vertical Distance Between Mounting Centers:**

3.800 inches

**Operating Temperature Rating:**

Between -20.0 degrees celsius and 70.0 degrees celsius

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

1.2 amperes resistive load second voltage and 1.2 amperes inductive load second voltage

**Contact Voltage Rating In Volts:**

65.0 ac at sea level first voltage

**Special Features:**

Hysteresis in the head-on mode shall be a of 5.0 percent and a of 40.0 percent of the sensing distances

**Test Data Document:**

81349-mil-s-24711 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0

**Mil-std (military Standard):**

Mil-s-24711 spec.