## NSN 5930-01-316-7366

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-316-7366 **Body Style:** Hole mounted **Actuator Style:** Round **Actuator Diameter:** 0.440 inches **Housing Height:** 2.080 inches **Housing Length:** 6.100 inches **Housing Width:** 2.720 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 4.130 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.500 inches **Maximum Voltage Rating In Volts:** 600.0 ac and 250.0 dc Inclosure Type: Fully enclosed Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.250 inches **Nonpile-up Contact Arrangement:** 2 two circuit, double break/double make, one position momentary single switch unit **Switch Actuating Force:** 64.0 inch-ounces **Actuator Movement:** 10.0 pretravel degrees and 90.0 overtravel degrees and 4.0 differential degrees **Contact Load Current Rating At Maximum Rated Voltage:** 110.000 milliamperes resistive dc and 110.000 milliamperes inductive dc and 1.500 amperes resistive ac and 1.500 amperes inductive ac **Precious Material And Location:** Contacts silver **Thread Series Designator:** Unc **Terminal Type And Quantity:** 8 screw

--

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5930-01-316-7366

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0