

View Online at <https://aerobasegroup.com/nsn/5930-01-316-8061>

Hazardous Locations/environmental Protection:

Humidity resistant

Unthreaded Mounting Hole Diameter:

0.161 inches single mounting facility

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

1.420 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.420 inches single mounting facility

Operating Temperature Range:

-10.0/+107.0 degrees fahrenheit

End Application:

6115-01-304-8183 generator set, diesel engine, trailer mounted

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob and legend plate

Contact Voltage Rating In Volts:

300.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

7 single actuator

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

12.0 amperes resistive load ac at sea level

Special Features:

Legend plate reads I3I1 I2I3 I1I2 off I1-n I2-n I3-n voltmeter

Precious Material And Location:

Contacts gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0