

View Online at <https://aerobasegroup.com/nsn/5930-01-316-8062>

Thread Class:

2b 1st mounting facility

Overall Length:

12.940 inches

Overall Height:

3.750 inches

Overall Width:

3.750 inches

Individual Section Quantity:

20

Longest Horizontal Distance Between Mounting Centers:

2.300 inches 1st mounting facility

Longest Vertical Distance Between Mounting Centers:

2.300 inches 1st mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

Throw Quantity:

12 each section periphery

Mounting Facility Circle Radius:

0.905 inches 2nd mounting facility

Mounting Method:

Threaded stud 2nd mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 1st mounting facility

Thread Size:

0.190 inches 2nd mounting facility

Contact Voltage Rating In Volts:

345.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular 1st mounting facility

Switch Actuator Indexing Position Quantity:

12 single actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

7.5 amperes resistive load lowest ac voltage rating at sea level

Special Features:

Item must comply with requirements of defense electronics supply center production standard no. L04174; for navy nuclear propulsion plant products only

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unf 2nd mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0