

View Online at <https://aerobasegroup.com/nsn/5930-01-316-8062>

**Thread Class:**

2b 1st mounting facility

**Overall Length:**

12.940 inches

**Overall Height:**

3.750 inches

**Overall Width:**

3.750 inches

**Individual Section Quantity:**

20

**Longest Horizontal Distance Between Mounting Centers:**

2.300 inches 1st mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.300 inches 1st mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section periphery

**Throw Quantity:**

12 each section periphery

**Mounting Facility Circle Radius:**

0.905 inches 2nd mounting facility

**Mounting Method:**

Threaded stud 2nd mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

24 1st mounting facility

**Thread Size:**

0.190 inches 2nd mounting facility

**Contact Voltage Rating In Volts:**

345.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular 1st mounting facility

**Switch Actuator Indexing Position Quantity:**

12 single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section periphery

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

7.5 amperes resistive load lowest ac voltage rating at sea level

**Special Features:**

Item must comply with requirements of defense electronics supply center production standard no. L04174; for navy nuclear propulsion plant products only

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unf 2nd mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0