# NSN 5930-01-316-8064

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-316-8064

# Thread Class:

2b single mounting facility

# Hazardous Locations/environmental Protection:

Shock proof

# Overall Length:

3.520 inches

# **Overall Height:**

1.740 inches

# **Overall Width:**

2.120 inches

# Individual Section Quantity:

1

## Knob Manufacturer Code:

27192

## Knob Manufacturer Part Number:

53-1160

## Longest Horizontal Distance Between Mounting Centers:

1.620 inches single mounting facility

## Longest Vertical Distance Between Mounting Centers:

1.250 inches single mounting facility

## Switch Contact Basic Design:

Nonpile-up nonsymmetrical

#### **Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

#### **Features Provided:**

Actuator knob and legend plate

#### Thready Qty Per Inch (tpi):

32 single mounting facility

#### **Thread Size:**

0.164 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

440.0 highest ac voltage rating at sea level

#### Switch Actuator Momentary Position:

Clockwise single actuator

#### Mounting Facility Pattern:

Four position rectangular single mounting facility

## Switch Actuator Indexing Position Quantity:

3 single actuator

**Terminal Type:** 

Tab w/screw

#### **Switch Actuator Positioning Increment:**

90.0 degrees single actuator

# NSN 5930-01-316-8064

Rotary Switch - Page 2 of 2



## Switch Actuator Stop Device Type:

Fixed stop single actuator

#### **Contact Load Current Rating:**

750.0 milliamperes inductive load highest ac voltage rating at sea level

#### **Special Features:**

Legend plate reads auto off stop

#### Style Designator:

Tap, circuit selector

#### Thread Series Designator:

Unc single mounting facility

#### Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A052b0