

View Online at <https://aerobasegroup.com/nsn/5930-01-316-8989>

**Unthreaded Mounting Hole Diameter:**

0.406 inches

**Longest Horizontal Distance Between Mounting Centers:**

3.000 inches

**Longest Vertical Distance Between Mounting Centers:**

3.000 inches

**Operating Temperature Rating:**

Between -4.0 degrees fahrenheit and 158.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Decrease

**Mounting Facility Pattern:**

Eight position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, double make, momentary action

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

1.25 amperes resistive load second voltage and 1.25 amperes inductive load second voltage

**Contact Adjustability:**

Actuation point not adjustable

**Contact Voltage Rating In Volts:**

65.0 ac at sea level first voltage

**Special Features:**

Sensing face 0.500 in.

**Frequency In Hertz:**

60.0 second voltage

**Test Data Document:**

Mil-s-24711 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0

**Mil-std (military Standard):**

Mil-s-24711 spec.