

View Online at <https://aerobasegroup.com/nsn/5930-01-316-8997>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Driptight and shock resistant

**Overall Length:**

2.345 inches

**Overall Height:**

0.750 inches

**Overall Width:**

0.750 inches

**Body Diameter:**

0.562 inches

**Bushing Length:**

Between 0.415 inches and 0.435 inches

**Body Length:**

1.050 inches

**Case Material:**

Metal

**Actuator Length:**

0.750 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.750 inches

**Actuator Width:**

0.750 inches

**Actuator Color:**

Black single actuator

**Illuminated Actuator Color:**

Black single actuator

**Actuator Inscription:**

Arrow symbol pointing to lower left corner single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 0.500 amperes inductive dc

**Special Features:**

White actuator inscription character appears red when illuminated

**Precious Material And Location:**

Contacts gold

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 turret and 5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0