

View Online at <https://aerobasegroup.com/nsn/5930-01-316-8997>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Driptight and shock resistant

Overall Length:

2.345 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

Body Diameter:

0.562 inches

Bushing Length:

Between 0.415 inches and 0.435 inches

Body Length:

1.050 inches

Case Material:

Metal

Actuator Length:

0.750 inches

Actuator Style:

Rectangular

Actuator Height:

0.750 inches

Actuator Width:

0.750 inches

Actuator Color:

Black single actuator

Illuminated Actuator Color:

Black single actuator

Actuator Inscription:

Arrow symbol pointing to lower left corner single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Special Features:

White actuator inscription character appears red when illuminated

Precious Material And Location:

Contacts gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0