## NSN 5930-01-316-9539

Rotary Switch - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5950-01-516-9559
Hazardous Locations/environmental Protection:
Moisture resistant
Overall Length:
5.530 inches
Overall Height:
3.250 inches
Overall Width:
2.810 inches
Unthreaded Mounting Hole Diameter:
0.221 inches single mounting facility
Individual Section Quantity:
3
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
02000-10
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
Shortest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.188 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob and legend plate
Contact Voltage Rating In Volts:
600.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:
5 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section periphery
Switch Actuator Positioning Increment:
45.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Adjustable stop single actuator

## NSN 5930-01-316-9539

Rotary Switch - Page 2 of 2



Contact Load	Current	Rating:
--------------	---------	---------

6.0 amperes resistive load highest ac voltage rating at sea level

**Special Features:** 

Legend plate reads off rec 1 rec 2 rec 3 rec 4

**Precious Material And Location:** 

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A052b0