

View Online at <https://aerobasegroup.com/nsn/5930-01-317-0563>

Unthreaded Mounting Hole Diameter:

0.406 inches

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Longest Vertical Distance Between Mounting Centers:

3.000 inches

Operating Temperature Rating:

Between -4.0 degrees fahrenheit and 158.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Decrease

Mounting Facility Pattern:

Eight position rectangular

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

250.0 milliamperes resistive load second voltage and 250.0 milliamperes inductive load second voltage and 100.0 milliamperes lamp load second voltage

Contact Adjustability:

Actuation point not adjustable

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Special Features:

Sensing face 0.500 in.

Test Data Document:

81349-mil-s-24711 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0

Mil-std (military Standard):

Mil-s-24711 spec.