

View Online at <https://aerobasegroup.com/nsn/5930-01-317-0564>

Unthreaded Mounting Hole Diameter:

0.406 inches

Longest Horizontal Distance Between Mounting Centers:

3.800 inches

Longest Vertical Distance Between Mounting Centers:

3.800 inches

Operating Temperature Rating:

Between -4.0 degrees fahrenheit and 158.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Decrease

Mounting Facility Pattern:

Eight position rectangular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

1.25 amperes resistive load second voltage and 1.25 amperes inductive load second voltage

Contact Adjustability:

Actuation point not adjustable

Contact Voltage Rating In Volts:

65.0 ac at sea level first voltage

Special Features:

Sensing face 1.500 in.

Frequency In Hertz:

60.0 second voltage

Test Data Document:

81349-mil-s-24711 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0

Mil-std (military Standard):

Mil-s-24711 spec.