## NSN 5930-01-317-0582

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-317-0582

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Driptight and dustproof
Overall Length:
0.960 inches
Overall Height:
2.360 inches
Overall Width:
0.960 inches
Body Length:
0.680 inches
Body Width:
0.680 inches
Body Height:
1.820 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.275 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator and white single actuator
Illuminated Actuator Color:
Blue single actuator and white single actuator
Actuator Inscription:
Catcc/call in single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
4 pole, double throw, one position momentary single switch unit

## NSN 5930-01-317-0582

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

**Special Features:** 

Horizontal split lens; t-1 lamp bulb size

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

12 turret and 6 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0