

View Online at <https://aerobasegroup.com/nsn/5930-01-317-1870>

**Hazardous Locations/environmental Protection:**

Humidity resistant

**Overall Height:**

1.890 inches

**Overall Width:**

1.890 inches

**Unthreaded Mounting Hole Diameter:**

0.161 inches single mounting facility

**Individual Section Quantity:**

4

**Longest Horizontal Distance Between Mounting Centers:**

1.420 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.420 inches single mounting facility

**Operating Temperature Range:**

-10.0/+107.0 degrees fahrenheit

**End Application:**

6115-01-304-8184 generator set, diesel engine, trailer mounted

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Features Provided:**

Actuator knob and legend plate

**Contact Voltage Rating In Volts:**

300.0 ac at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

7 single actuator

**Terminal Type:**

Screw

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

12.0 amperes resistive load ac at sea level

**Special Features:**

Legend plate reads off 1 2 3 ammeter

**Precious Material And Location:**

Contacts gold

**Precious Material:**

Gold

**Style Designator:**

Tap, circuit selector

**Specification Data:**

81381-99112 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0