

View Online at <https://aerobasegroup.com/nsn/5930-01-317-1882>

Thread Class:

2a

Body Style:

Bushing mounted

Body Diameter:

0.562 inches

Bushing Length:

0.297 inches

Body Length:

0.465 inches

Actuator Diameter:

0.375 inches

Actuator Height:

0.391 inches

Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.500 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, double make, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab, solder lug

Specification Data:

81349-mil-s-8805/107 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A053a0