## NSN 5930-01-317-3089

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-317-3089

## **Thread Class:**

2b single mounting facility

## Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

## **Overall Length:**

8.253 inches

## **Overall Height:**

3.688 inches

#### **Overall Width:**

4.375 inches

## Individual Section Quantity:

10

#### Switch Contact Basic Design:

Nonpile-up nonsymmetrical

## **Mounting Facility Circle Radius:**

1.609 inches single mounting facility

## **Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

## Features Provided:

Actuator knob and dummy section

## Thready Qty Per Inch (tpi):

20 single mounting facility

#### **Thread Size:**

0.250 inches single mounting facility

## **Contact Voltage Rating In Volts:**

500.0 ac at sea level

## **Mounting Facility Pattern:**

Four position circular single mounting facility

## Switch Actuator Indexing Position Quantity:

2 single actuator

#### **Terminal Type:**

Tab w/screw

## **Contact Switching Action:**

Makes before breaks each section periphery

## Switch Actuator Positioning Increment:

90.0 degrees single actuator

## Switch Actuator Stop Device Type:

Fixed-adjustable stops single actuator

## **Contact Load Current Rating:**

30.0 amperes resistive load lowest dc voltage rating at sea level

## Style Designator:

Tap, circuit selector

# NSN 5930-01-317-3089

Rotary Switch - Page 2 of 2



Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0

