## NSN 5930-01-317-3542

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-317-3542

view Online at https://derobasegroup.com/nish/0550-01-517-5042
Overall Length:
3.278 inches
Outside Diameter:
0.313 inches all connections
Overall Height:
4.500 inches
Overall Width:
3.500 inches
Unthreaded Mounting Hole Diameter:
0.170 inches
Longest Horizontal Distance Between Mounting Centers:
3.062 inches
Longest Vertical Distance Between Mounting Centers:
4.062 inches
Pressure Switch Type:
Differential
Operating Tempurature Rating:
Between -40.0 degrees fahrenheit and 150.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Contact Action Stimulus:
Decrease
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
5.0 amperes resistive load second voltage and 3.0 amperes inductive load second voltage
Contact Adjustability:
Actuation point not adjustable
Contact Stimulus Rating:
1.40 actuation point inches of water
Contact Voltage Rating In Volts:
28.0 dc at sea level second voltage
Pressure Connector Type:
Plain, unthreaded external all connections

Media For Which Designed:

Frequency In Hertz: 60.0 first voltage

Gas

## **NSN 5930-01-317-3542**Pressure Switch - Page 2 of 2



<b>Precious Material And Location:</b>
Contacts silver
Precious Material:
Silver
Style Designator:
Rectangular w/bracket
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0