

View Online at <https://aerobasegroup.com/nsn/5930-01-317-4087>

Thread Class:

2a

Body Style:

Bushing mount

Overall Length:

0.500 inches

Overall Height:

1.333 inches

Overall Width:

0.450 inches

Bushing Length:

0.378 inches

Body Length:

0.500 inches

Body Width:

0.450 inches

Body Height:

0.410 inches

Case Material:

Plastic

Actuator Style:

Rectangular

Actuator Height:

0.450 inches

Actuator Width:

0.100 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes resistive ac

Special Features:

Actuator has antirotation feature

Precious Material And Location:

Contact and terminal surfaces silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0