

View Online at <https://aerobasegroup.com/nsn/5930-01-317-5076>

Hazardous Locations/environmental Protection:

Watertight and dustproof

Overall Length:

5.812 inches

Overall Height:

6.750 inches

Overall Width:

2.688 inches

Body Length:

5.000 inches

Body Height:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Mounting Facility Centers:

5.250 inches

Pressure Switch Type:

Differential

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

160.00 pounds per square inch gage

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes motor load third voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+7.00/+70.00 actuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level fourth voltage

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0