

View Online at <https://aerobasegroup.com/nsn/5930-01-317-5080>

Thread Class:

2a

Body Style:

Bushing mount

Overall Length:

0.572 inches

Overall Height:

2.256 inches

Overall Width:

0.556 inches

Bushing Length:

0.469 inches

Body Length:

0.572 inches

Body Width:

0.556 inches

Actuator Style:

Round

Actuator Diameter:

0.430 inches

Actuator Height:

0.837 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary and center position maintained

Actuator Position-locking Relationship:

Up position locked in and out and down position no locking action and center position no locking action

Maximum Voltage Rating In Volts:

115.0 ac and 50.0 dc

Mounting Surface To Terminal End Distance:

0.950 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary, two positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 2.000 amperes resistive ac

Precious Material And Location:

Terminal surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 printed circuit

Specification Data:

13499-266-5077 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0