

View Online at <https://aerobasegroup.com/nsn/5930-01-317-6548>

Inside Diameter:

0.250 inches single connection

Overall Length:

4.875 inches

Overall Height:

5.312 inches

Overall Width:

2.625 inches

Body Length:

4.625 inches

Body Height:

2.500 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Longest Horizontal Distance Between Mounting Centers:

2.406 inches

Shortest Horizontal Distance Between Mounting Centers:

0.656 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

160.00 pounds per square inch gage

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes resistive load eighth voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+7.00/+70.00 actuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point shaft with scale

Contact Voltage Rating In Volts:

550.0 dc at sea level fifth voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 third voltage

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0