NSN 5930-01-317-6555

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-317-6555

Thread Class:

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

Overall Length:

5.626 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.625 inches single actuator

Overall Diameter:

2.188 inches

Individual Section Quantity:

7

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

End Application:

5840-00-220-5690 radar set an/tps-32

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

9 each section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

9 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks 7th section rear

NSN 5930-01-317-6555

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

60.0 degrees single actuator

Contact Load Current Rating:

0.5 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0