

View Online at <https://aerobasegroup.com/nsn/5930-01-317-6557>

**Overall Length:**

8.907 inches

**Overall Height:**

6.000 inches

**Overall Width:**

4.750 inches

**Unthreaded Mounting Hole Diameter:**

0.406 inches single mounting facility and 0.410 inches single mounting facility

**Individual Section Quantity:**

8

**Longest Horizontal Distance Between Mounting Centers:**

3.781 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

3.781 inches single mounting facility

**End Application:**

5865-01-236-4235 mobile electronic warfare system an/mlq-36

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

500.0 ac at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Contact Load Current Rating:**

60.0 amperes resistive load dc at sea level

**Style Designator:**

Tap, square frame

**Test Data Document:**

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-s-15291/9 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0