

View Online at <https://aerobasegroup.com/nsn/5930-01-317-6558>

**Thread Class:**

2b 1st mounting facility

**Thread Length:**

0.312 inches 3rd mounting facility

**Overall Length:**

5.657 inches

**Overall Height:**

4.125 inches

**Overall Width:**

4.375 inches

**Unthreaded Mounting Hole Diameter:**

0.312 inches 2nd mounting facility

**Distance Between Mounting Facility Centers:**

3.812 inches 2nd mounting facility

**Individual Section Quantity:**

8

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Facility Circle Radius:**

1.610 inches 1st mounting facility

**Mounting Method:**

Threaded bushing 3rd mounting facility

**Features Provided:**

Actuator knob and dummy section

**Thready Qty Per Inch (tpi):**

20 1st mounting facility

**Thread Size:**

0.625 inches 3rd mounting facility

**Contact Voltage Rating In Volts:**

500.0 ac at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator

**Mounting Facility Pattern:**

Two position in-line 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab w/screw

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

30.0 amperes resistive load dc at sea level

**Special Features:**

Item must comply with requirements of defense electronics supply center production standard no. L04199; for navy nuclear propulsion plant products only

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unef 3rd mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0