

View Online at <https://aerobasegroup.com/nsn/5930-01-317-6558>

Thread Class:

2b 1st mounting facility

Thread Length:

0.312 inches 3rd mounting facility

Overall Length:

5.657 inches

Overall Height:

4.125 inches

Overall Width:

4.375 inches

Unthreaded Mounting Hole Diameter:

0.312 inches 2nd mounting facility

Distance Between Mounting Facility Centers:

3.812 inches 2nd mounting facility

Individual Section Quantity:

8

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

1.610 inches 1st mounting facility

Mounting Method:

Threaded bushing 3rd mounting facility

Features Provided:

Actuator knob and dummy section

Thready Qty Per Inch (tpi):

20 1st mounting facility

Thread Size:

0.625 inches 3rd mounting facility

Contact Voltage Rating In Volts:

500.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator

Mounting Facility Pattern:

Two position in-line 2nd mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

30.0 amperes resistive load dc at sea level

Special Features:

Item must comply with requirements of defense electronics supply center production standard no. L04199; for navy nuclear propulsion plant products only

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unef 3rd mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0