NSN 5930-01-318-2809

Thermostatic Switch - Page 1 of 2

N/a



| View Online at https://aerobasegroup.com/nsn/5930-01-318-2809 |
|---|
| Thread Class: |
| 3a single threaded bushing |
| Thread Length: |
| 0.440 inches single threaded bushing |
| Hazardous Locations/environmental Protection: |
| Waterproof |
| Overall Length: |
| 3.880 inches |
| Body Diameter: |
| 0.250 inches |
| Body Length: |
| Between 2.200 inches and 2.300 inches |
| Tempurature Sensing Element Type: |
| Bulb |
| Width Across Flats: |
| 0.870 inches |
| Mounting Method: |
| Threaded bushing |
| Contact Action Stimulus: |
| Increase |
| Thread Size: |
| 0.500 inches single threaded bushing |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Terminal Type: |
| Tab w/screw |
| Contact Load Current Rating: |
| 1.5 amperes resistive load single voltage and 500.0 milliamperes inductive load single voltage |
| Contact Adjustability: |
| Actuation point not adjustable and deactuation point not adjustable |
| Contact Stimulus Rating: |
| 150.00 actuation point degrees fahrenheit and 170.00 actuation point degrees fahrenheit and 145.00 deactuation point degrees fahrenheit |
| and 165.00 deactuation point degrees fahrenheit |
| Contact Voltage Rating In Volts: |
| 28.0 dc at sea level single voltage |
| Media For Which Designed: |
| Gas or liquid |
| Style Designator: |
| Cylindrical w/flange |
| Thread Series Designator: |
| Unf all threaded bushing |
| Shelf Life: |

NSN 5930-01-318-2809

Thermostatic Switch - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A048b0