

View Online at <https://aerobasegroup.com/nsn/5930-01-318-4448>

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Height:**

0.360 inches

**Body Diameter:**

0.660 inches

**Mounting Slot Width:**

0.104 inches

**Distance Between Mounting Facility Centers:**

Between 0.930 inches and 0.944 inches

**Temperature Sensing Element Type:**

Internal sensor

**Operating Temperature Rating:**

Between -10.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Mounting Method:**

Bracket and slot

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 1.0 amperes lamp load second voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

120.00 actuation point degrees fahrenheit and 116.00 deactuation point degrees fahrenheit and 118.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Disc

**Test Data Document:**

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical" "average" "" etc.)

**Specification Data:**

81349-mil-s-24236/20 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0