

View Online at <https://aerobasegroup.com/nsn/5930-01-318-7862>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.360 inches single mounting facility and 0.390 inches single mounting facility

**Overall Length:**

1.743 inches

**Overall Height:**

1.700 inches

**Overall Width:**

Between 1.615 inches and 1.635 inches

**First Flat Length:**

0.360 inches single actuator and 0.390 inches single actuator

**Flat Height:**

0.208 inches single actuator and 0.228 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.610 inches single actuator and 0.640 inches single actuator

**Nonturn Device Radius:**

0.531 inches at 6:00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Key at 6:00 o'clock

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Coded

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Metallic inclosure

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level

**Switch Actuator Indexing Position Quantity:**

32 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Printed circuit

**Switch Actuator Positioning Increment:**

11.25 degrees single actuator

**Detent Rotational Torque Range:**

+14.000/+24.000 inch-ounces single actuator

**Contact Load Current Rating:**

125.0 milliamperes resistive load ac at sea level

**Contact Arrangement Truth Table:**

Special single section

**Special Truth Table Identification:**

94117-235038p2 single section

**Special Features:**

Programmable

**Precious Material And Location:**

Pcb surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular panel mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0