

View Online at <https://aerobasegroup.com/nsn/5930-01-318-7862>

Thread Class:

2a single mounting facility

Thread Length:

0.360 inches single mounting facility and 0.390 inches single mounting facility

Overall Length:

1.743 inches

Overall Height:

1.700 inches

Overall Width:

Between 1.615 inches and 1.635 inches

First Flat Length:

0.360 inches single actuator and 0.390 inches single actuator

Flat Height:

0.208 inches single actuator and 0.228 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.610 inches single actuator and 0.640 inches single actuator

Nonturn Device Radius:

0.531 inches at 6:00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Key at 6:00 o'clock

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Switch Contact Basic Design:

Coded

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Metallic inclosure

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Switch Actuator Indexing Position Quantity:

32 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Printed circuit

Switch Actuator Positioning Increment:

11.25 degrees single actuator

Detent Rotational Torque Range:

+14.000/+24.000 inch-ounces single actuator

Contact Load Current Rating:

125.0 milliamperes resistive load ac at sea level

Contact Arrangement Truth Table:

Special single section

Special Truth Table Identification:

94117-235038p2 single section

Special Features:

Programmable

Precious Material And Location:

Pcb surfaces silver

Precious Material:

Silver

Style Designator:

Rectangular panel mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0