

View Online at <https://aerobasegroup.com/nsn/5930-01-318-7863>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Bushing Length:**

0.470 inches

**Body Length:**

1.100 inches

**Body Width:**

0.670 inches

**Body Height:**

1.100 inches

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Diameter:**

0.953 inches

**Actuator Height:**

1.580 inches

**Actuator Position-action Relationship:**

Up position momentary and down position maintained and center position maintained

**Actuator Position-locking Relationship:**

Up position locked out and down position locked out and center position locked in

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 3.300 amperes motor ac and 2.000 amperes lamp ac

**Special Features:**

Pull to unlock

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

12 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0