

View Online at <https://aerobasegroup.com/nsn/5930-01-318-7863>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

0.470 inches

Body Length:

1.100 inches

Body Width:

0.670 inches

Body Height:

1.100 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.953 inches

Actuator Height:

1.580 inches

Actuator Position-action Relationship:

Up position momentary and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position locked out and down position locked out and center position locked in

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 3.300 amperes motor ac and 2.000 amperes lamp ac

Special Features:

Pull to unlock

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0