NSN 5930-01-318-8081

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-318-8081
Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.875 inches
Body Length:
1.094 inches
Body Width:
0.400 inches
Body Height:
0.625 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.126 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.406 inches
Actuator Length:
2.340 inches
Actuator Style:
Leaf
Actuator Width:
0.170 inches
Actuator Free Position Height:
0.600 inches
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

3.0 grams

Switch Actuating Force:

40.0 grams

Actuator Movement:

Between 0.210 pretravel inches and 0.160 overtravel inches and 0.060 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

 $250.000 \ \mbox{milliamperes}$ resistive dc and $15.000 \ \mbox{amperes}$ resistive ac

NSN 5930-01-318-8081

Sensitive Switch - Page 2 of 2



Terminal Type Ar	nd Quantity:
------------------	--------------

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0