

View Online at <https://aerobasegroup.com/nsn/5930-01-318-9640>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Waterproof

Overall Length:

1.585 inches

Body Diameter:

0.500 inches

Bushing Length:

Between 0.225 inches and 0.245 inches

Body Length:

Between 0.440 inches and 0.470 inches

Overall Diameter:

0.750 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.750 inches

Actuator Height:

Between 0.635 inches and 0.695 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thread Size:

0.375 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes resistive dc

Precious Material And Location:

Contacts gold

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0