NSN 5930-01-319-3028

Hazardous Locations/environmental Protection:

Pressure Switch - Page 1 of 2

Inside Diameter:

Vibration resistant

0.250 inches single connection



View Online at https://aerobasegroup.com/nsn/5930-01-319-3028

Overall Length:
3.500 inches
Overall Height:
7.750 inches
Overall Width:
2.630 inches
Body Height:
3.600 inches
Unthreaded Mounting Hole Diameter:
0.270 inches
Longest Horizontal Distance Between Mounting Centers:
2.720 inches
Longest Vertical Distance Between Mounting Centers:
2.720 inches
Pressure Switch Type:
Differential
Mounting Method:
Base and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Decrease
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position diagonal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
600.0 milliamperes inductive load second voltage
Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:
+20.00/+1000.00 actuation point pounds per square inch gage
Contact Adjustment Type:
Internal actuation point knob with scale

NSN 5930-01-319-3028

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts: 600.0 ac at sea level second voltage Pressure Connector Type: Plain, threaded internal single connection Media For Which Designed: Gas or liquid Style Designator:

Rectangular

Thread Series Designator:

Nptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0