NSN 5930-01-319-3037

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-319-3037

| Body Style: |
|--|
| Bushing mount |
| Hazardous Locations/environmental Protection: |
| Dustproof |
| Overall Length: |
| 0.775 inches |
| Overall Height: |
| 2.828 inches |
| Overall Width: |
| 0.650 inches |
| Bushing Length: |
| 0.468 inches |
| Body Length: |
| 0.775 inches |
| Body Width: |
| 0.650 inches |
| Body Height: |
| 1.120 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.420 inches |
| Actuator Height: |
| 1.140 inches |
| Actuator Position-action Relationship: |
| Up position momentary and down position momentary and center position maintained |
| Actuator Position-locking Relationship: |
| Up position locked out and down position no locking action and center position no locking action |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| End Application: |
| Aircraft, eagle f-15 |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Features Provided: |
| Actuator seal |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.469 inches |

NSN 5930-01-319-3037

Toggle Switch - Page 2 of 2



| Nonnile-un | Contact | Arrangement: |
|--------------|---------|--------------|
| 14011pile-up | Contact | Arrangement. |

4 pole, double throw, two positions momentary single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0