NSN 5930-01-319-3038

Hazardous Locations/environmental Protection:

Sensitive Switch - Page 1 of 2

Shock resistant and vibration resistant

Body Style:Hole mounted



View Online at https://aerobasegroup.com/nsn/5930-01-319-3038

Overall Height:
2.790 inches
Overall Width:
Between 0.590 inches and 0.650 inches
Body Length:
1.660 inches
Body Width:
Between 0.590 inches and 0.650 inches
Body Height:
Between 2.070 inches and 2.110 inches
Unthreaded Mounting Hole Diameter:
0.138 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.812 inches
Actuator Style:
Round
Actuator Diameter:
0.250 inches
Actuator Height:
0.213 inches
Actuator Free Position Height:
0.375 inches
Maximum Voltage Rating In Volts:
115.0 ac and 250.0 dc
End Application:
5840-01-017-8558 radar set
Inclosure Type:
Uninclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Actuator Movement:
0.188 pretravel inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 100.000 milliamperes resistive dc and 10.000 amperes resistive ac
Terminal Type And Quantity:
6 tab w/screw

NSN 5930-01-319-3038

Sensitive Switch - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0